



PROTECT

8901



2922

710026009
L 32,31 / LRV 7,22




8901

710026008
L 16,56 / LRV 2,21



9021

710026007
L 23,18 / LRV 3,85



9990

710026006
L 21,55 / LRV 3,39

TECHNICAL DATA

	Standards	Protect
Classification		
Product code		A076
Type of manufacture	ISO 2424	Tufted 1/8"
Aspect	ISO 2424	Cut pile
Dye method		Hank dyed
Dimension	EN ISO 24342	50 cm x 50 cm / 19,68" x 19,68" (16 tiles per box)
Primary backing	ISO 2424	Polyester fleece
Secondary backing	ISO 2424	DESSO ProBase - modified bitumen
Pile fibre composition	ISO 2424	80% wool - 20% polyamide
Total thickness	ISO 1765	10.0 mm 0.4 inch
Effective pile thickness	ISO 1766	5.2 mm 0.20 inch
Total mass	ISO 8543	4800 g/m ² 141.7 oz/yd ²
Total pile mass	ISO 2424	1470 g/m ² 43.4 oz/yd ²
Effective pile mass	ISO 8543	790 g/m ² 23.3 oz/yd ²
Pile density	ISO 8543	0.152 g/cm ³ 0.0055 lb/in ³
Number of tufts	ISO 1763	1110 /dm ² 92807 /yd ²
Flammability	EN 13501-1	C _{fl} - s1 (loose laid tested)
Light Reflectance Value (LRV)	BS 8493	See left page per colour
Colour Depth (L)	CIELAB	See left page per colour

Logistics information	Laying direction	Labels & Certifications
	